



AE-DO10

Dissolved Oxygen Tester 10sets Memory

Key Features

1. Easy Maintenance, no tools needed to change batteries and electrode;
2. Auto-off function, data-hold function and low-batteries indicator;
3. High quality multi-function carrying case;
4. Stability Auto-Hold function;
5. Electrode slope indicator display.

Product Description

Feature of Dissolved Oxygen Meter :

1. Extensive application : Aquacultural: Use to monitor oxygen levels in ornament fish tanks and ponds; fish and shells farming;
2. Display: Large LCD screen with backlit for easy reading, provides comprehens meter information;
3. Easy Maintenance, no tools needed to change batteries and electrode;
4. Auto-off function, data-hold function and low-batteries indicator;
5. High quality multi-function carrying case;
6. Stability Auto-Hold function;
7. Electrode slope indicator display.



Technical Specifications:

Model	AE-DO10
Measurement Range	0.00~20.00mg/L, 0.0~200.0%
Temperature Range	0~60°C/32~140°F
Resolution	0.01mg/L /0.1% / 0.1°C/0.1°F
Accuracy	±1.5%F.S. ±0.3°C/0.5°F
Temperature Compensation	0.0~60°C/32~140°F
Atmospheric Pressure Compensation	600~1100mbar
Salinity Compensation	0.0~40.0ppt
Ingress Protection	IP67
Calibration	1 or 2 points
Electrode	AE-DO10-1
Power Supply	1×1.5V AAA
Memory	10sets
Display	22x32mm Photo-Luminescent LCD
Dimensions/Weight	164x37x40mm/90g
Remark	—



Tester Accessories(AE-DO10-1):

Galvanic DO Electrode
Type: Platinum Cathode/Alloy Anode
Temperature System: NTC22K
Test Range: 0~20mg/L
Temperature Range: 0~60°C