

1342 / 1343 DIGI-MET® Workshop calipers IP65



1



Model

- Stainless steel
- Inductive measuring system, resistant to damp and sweat
- DIN 862
- Knife points
- LCD display:
10 mm with measuring range 300 mm;
12.5 mm from measuring range 500 mm
- Locking screw

Functions

- ON / OFF
- Quick-Start
- Quick-Lock (key lock)
- Set to zero at any point
- mm / inch switching
- PRESET - Function (setting a numerical value)
- Variable data output RS 232 + Digimatic + US

Delivery

- Wooden case

		Measuring range		Jaw length		Reading		Stepped jaws	Error limit	Order no.
		mm	inch	mm	inch	mm	inch	mm	mm	
With knife paints, without fine adjustment										
•		0-300	0-12	90	3.5	0.01	.0005	10	0.03	1342 522
•		0-500	0-20	125	5.0	0.01	.0005	20	0.03	1342 528
•		0-800	0-31	150	6.0	0.01	.0005	20	0.04	1342 532
•		0-1000	0-39	150	6.0	0.01	.0005	20	0.04	1342 534
With knife points, with fine adjustment										
•		0-300	0-12	90	3.5	0.01	.0005	10	0.03	1343 522
•		0-500	0-20	125	5.0	0.01	.0005	20	0.03	1343 528
•		0-800	0-31	150	6.0	0.01	.0005	20	0.04	1343 532
•		0-1000	0-39	150	6.0	0.01	.0005	20	0.04	1343 534



Accessories

Accessories	Order no.
Battery, 3V-Lithium, CR 2032	0220 704
Data cable DATA VARIABLE to USB	1998 720
Data cable DATA VARIABLE to RS232	1997 501
Data cable DATA VARIABLE to Digimatic	1998 501

