



B.N.C.TOOLING Co.,Ltd.

BNCTOOLING.COM
BNCTOOLINGSHOP.COM



HELIOS • PREISSER

1730 / 1732 DIGI-MET ° Indicators



1730 502



1730 506

Model

- Aluminium housing
- Outer ring (Bezel) Ø 60 mm
- Replacement probe tip
- M 2.5
- Protection class IP54
- Clamping shank Ø 8 mm
- Display unit can be rotated through 280°
- LCD display with 11 mm high numerals
- Factory standard

Functions

- ON / OFF
- Quick-Start
- Quick-Lock (key lock)
- Set to zero at any point mm / inch switching
- ABS (display can be set to zero without losing the Preset value)
- TOL (tolerance value input)
- Reversal of counting direction

Delivery

- Cardboard box

- Factor input
- Individual key lock
- PRESET-Function (setting a numerical value)
- Variable data output RS 232 + Digimatic + USB

Measuring span	Resolution		Error limit		Repeatability	Measuring force	Order no.
	mm	mm	inch	total span mm			
12.5	0.001	.00005	0.004	0.002	0.001	0.65 - 0.9	1730 502
25	0.001	.00005	0.004	0.002	0.001	0.65 - 1.15	1730 506

* Reading switchable: 0.0005 / 0.001 / 0.002 / 0.005 / 0.010 mm

** Partial span= 25 steps by step value 0.0005 mm



1998720

1998501

1997501

Accessories

Accessories	Order no.
Battery, 3V-Lithium, CR 2450	1998 770
Data cable Data Variable to USB	1998 720
Data cable Data Variable to RS232	1997 501
Data cable Data Variable to digimatic	1998 501
Cable release (12,5 mm)	

Marked * = excess length/excess weight

Marked * = includes a F.O.C. calibration certificate, traceable to national standards