

69/90 Hatairat Rd., Minburi , Minburi Bangkok (Thailand) 10510



# **SJV Series Electric Vertical Test Stand**

SJV Series Electric Vertical Test Stand has good stability, wide application, convenient usage. This test stand, equipped with push pull force gauge, can be fitted to perform tension/compression test, insertion/withdraw test and destructive test.

### SJV-5K

- Dimension: L \* W X H(mm) 410 X 260 X 1030. Testing speed: 30-240(mm/min); Stroke: 200mm; Weight: about 54.8kg; Capacity: 5000N.
- Can be configured (purchase additionally): SN/SKN, SH/SP(2N-5KkN) push pull force gauge, various clamps.

### SJV-10K

- Dimension: LX W X H(mm) 410X260 X 1330.
- Testing speed: Bracket(24, 48, 72, 96, 120)mm/min; Stroke: 200mm; Weight: About 58.1kg; Capacity: 10000N.
- Can be configured (purchase additionally): SN/SKN, SH/SP(2N-10kN) push pull force gauge, various clamps.







SJV-5K (SKN)

SJV-5K (SH)

SJV-10K (SH)

# SJS Series Stepper Motor Test Stand

SJS Series Adopt Stepper Motor. Good stabiliy, wide application, wide and accurate test speed, stepless speed adjustment, manual operation and automatic cycle. Matched to force gauge and software, it could reach data test and stand control by computer. It could test tension/compression, insertion/withdraw, fatigue test, destructive test.

### SJS-500V

- Dimension:L X W XH (mm)380 X 286 X 680; Weight:about26kg;Capacity:500N;Stroke:300mm.
- Testing speed: 1-500mm/min;speed resolution: 1mm/min.
- Can be configured(purchase additionally):SH/SP(2N-500N)force gauge, various clamps.

## SJS-1KV

- Dimension:L X W XH (mm)410 X 270 X 970; Weight:about32kg;Capacity: 1000N;Stroke:520mm.
- Testing speed: 1-500mm/min; speed resolution: 1mm/min.
- Can be configured(purchase additionally):SH/SP(2N-1000N)force gauge, various clamps.

### SJS-2KV

- Dimension:Lx WxH (mm)465 X 310 X 1180; Weight:about53kg;Capacity:2000N;Stroke:600mm.
- Testing speed: 1-500mm/min; speed resolution: !mm/min.
- Can be configured(purchase additionally):SH/SP(2N-2000N)force gauge, various clamps.

### SJS-IKVL

- Dimension:Lx WxH (mm)380 X 285 X 1490; Weight:about57kg;Capacity: 1000N;Stroke:1000mm.
- Testing speed: 1-500mm/min; speed resolution: 1mm/min.
- Can be configured(purchase additionally):SH/SP(2N-1000N)force gauge, various clamps.



SJX-500V (SP)



SJX-1KV (SP)



SJX-2KV (SP)



SJX-1KVL(SP)

Note: the appearance and color depends on the real product.