



HELIOS · PREISSER

1320 DIGI-MET® Pocket calipers



1320 416



1320 517



Model

- Inductive measuring system, resistant to moisture and sweat
- Stainless steel
- LCD display 11 mm without data output, 7.5 mm with data output
- DIN 862
- Locking screw
- Inside cross points

- Four way measurement with measuring ranges 150 and 200 mm
- Three way measurement with measuring range 300 mm

Functions

- ON / OFF
- Quick-Start
- Quick-Lock (key lock)
- Set to zero at any point mm / inch switching
- PRESET- Function (setting a numerical value)

Delivery

- Plastic case



Video
electronic

PK		Measuring range		Jaw length		Reading		Error limit	Depth gauge	Order no.
		mm	inch	mm	inch	mm	inch	mm		
Without data output										
•		0-150	0-6	40	1.6	0.01	.0005	0.03	round 1.5	1320 416
•		0-150	0-6	40	1.6	0.01	.0005	0.03	rectangular	1320 417
With DATA VARIABLE										
•		0-150	0-6	40	1.6	0.01	.0005	0.03	round 1.5	1320 516
•		0-150	0-6	40	1.6	0.01	.0005	0.03	rectangular	1320 517
•		0-200	0-8	50	2.0	0.01	.0005	0.03	rectangular	1320 519
•		0-300	0-12	65	2.5	0.01	.0005	0.03	none	1320 522
With DATA VARIABLE, with extra long cross points (40 mm)										
•		0-150	0-6	40	1.6	0.01	.0005	0.03	round 1.5	1320 518

More information on 1320 518 on page 58



1998720

1998501

1997501

Accessories

Battery, 3V-Lithium, CR 2032	0220 704
Data cable DATA VARIABLE to digimatic	1998 501
Data cable DATA VARIABLE to RS232	1997 501
Data cable DATA VARIABLE to USB	1998 720