

69/90 Hatairat Rd., Minburi ,Minburi Bangkok (Thailand) 10510



S

SJX Series Electric Test Stand

SJX Series Electric Test Stand, equipped with push pull force gauge, can be fitted to perform a variety of force tests, such as tension/compression test, insertion/withdraw test, fatigue test and destructive test. In addition, It has stepless speed uniform motion, manual & automatic control switch functions and can preset the cycle test times. When equipped with SH series, it can preset the stopping force value.

SJX-5KV

- Dimension: L X W X H(mm) 410 X 260 X 1030; Stroke: 200mm; Weight: about 54.8kg; Capacity: 5000N; Testing speed: 30-240mm/min.
- Can be configured (purchase additionally): SN/SKN, SH/SP(2N-5kN) push pull force gauge, various clamps.

SJX-10KV

- Dimension: L X W X H(mm) 410 X 260 X 1330; Stroke: 200mm; Weight: about 59.5kg; Capacity: 10000N; Testing Speed: 20-120mm/min.
- Can be configured (purchase additionally): SN/SKN, SH/SP(2N-10kN)push pull force gauge, various clamps.

SJX-20KV

- Dimension: L X W X H(mm) 410 X 260 X 1080; Stroke: 200mm; Weight: about 63.5kg; Capacity: 20000N; Testing Speed: 20-120mm/min.
- Can be configured (purchase additionally): SH/SP(1kN-20kN) push pull force gauge, various clamps.

SJX-30KV

- Dimension: L X W X H(mm) 410 X 260 X 1080; Stroke: 200mm; Weight: about 63.5kg; Capacity: 30000N; Testing Speed: 8-75mm/min.
- Can be configured (purchase additionally): SH/SP(1kN-30KN) push pull force gauge, various clamps.



SJX-5KV (SP)



SJX-10KV (SP)



SJX-20KV~30KV (SP)

SJX-500V

- Dimension: LX W XH (mm) 430X245 X 570mm; Stroke: 250mm; Weight: about 24.2kg.
- Testing Speed: 50-245mm/min, max load: 200N; 250-500mm/min, max load: 500N.
- Can be configured (purchase additionally): SN, SH/SP (Sensor Inside) push pull force gauge, various clamps.

SJX-1KV

- Dimension: LX W XH (mm) 410X270X970mm; Stroke: 520mm; Weight: about 31.5kg.
- Testing Speed: 50-245mm/min, max load: 500N; 250-500mm/min, max load: 1000N.
- Can be configured (purchase additionally): SN, SH/SP (2N-1kN) push pull force gauge, various clamps.

SJX-2KV

- Dimension: LX W XH (mm) 465 X310X 1180mm; Stroke: 600mm; Weight: about 52.1kg.
- Testing Speed: 50-500mm/min, max load: 2000N.
- Can be configured (purchase additionally): SN, SH/SP (2N-2kN) push pull force gauge, various clamps.

SJX-IKVL

- Dimension: LX W XH (mm) 380X285 X 1490mm; Stroke: 1000mm; Weight: about 57.0kg.
- Testing Speed: 50-500mm/min, max load: 1000N.
- Can be configured (purchase additionally): SN, SH/SP (2N-1kN) push pull force gauge, various clamps.



SJX-500V (SP)



SJX-1KV (SP)



SJX-2KV (SP)



SJX-1KVL(SP)

Note: the appearance and color depends on the real product.

