

69/90 Hatairat Rd., Minburi , Minburi Bangkok (Thailand) 10510



## **Basic Manual Video Measuring System YF Series**



## I. Usage

YF Series is the basic type manual Video Measuring System developed by Yihui. It has been widely used in machinery, electronics, aerospace, automotive, military, mould, and other industries for precision measurement.

## II. Features

- 1. It adopts TEO™ 1 / 3" color CCD camera, the cross-line generator is the measuring aiming system.
- 2. Digital measurement and data processing system are made up by the two coordinate's studio, the optical grating and the SDK series data card.
- 3. It has RS-232 interface with a computer and specialized measurement software which can also processes and output circular mapping. Measurement data can be directly transformed into AutoCAD file and become a full work circle; the data also can be entered in Excel and Word to conduct statistical analysis.
- 4. Grade 00 JINANQING granite base and column, high stability.

| Model  |                         | YF-2010  | YF-3020     | YF-4030      | YF-5040       |
|--|-------------------------|--|-------------|--------------|---------------|
| Worktable  | Metal Table<br>Size(mm) | 404*228  | 500*330     | 606*466      | 706*606       |
|  | Glass<br>Table Size(mm) | 260*160  | 350*280     | 450*350      | 550*450       |
|  | XY Stroke(mm)           | 200*100  | 300*200     | 400*300      | 500*400       |
| Weight(kg)   |                         | 180  | 260         | 315          | 500           |
| Dimension(L*W*H, mm)                                 |                         | 556*540*860  | 670*660*950 | 720*950*1020 | 800*1040*1020 |
| Measuring Targeting System<br>(Standard Accessories) |                         | Camera :1 / 3" Color CCD Camera  |             |              |               |
|  |                         | Zoom Lens: professional optical lens,<br>magnification :0.7~4.5X WD:92mm |             |              |               |
|  |                         | Video Magnification:30~190X Object view:7~1.1mm                          |             |              |               |
|  |                         | Scale Resolution:0.5/0.1µm   |             |              |               |
| Z Stroke (mm)  |                         | 150mm  |             |              |               |
| Accuracy E1*   |                         | Ex, y ≤ (3.0+L/200) µm   |             |              |               |
| Accuracy E2*   |                         | Exy ≤ (4.0+L/200) µm   |             |              |               |
| Illumination   |                         | Surface light and transmission light adopt LED, brightness adjustable    |             |              |               |
| Power  |                         | 110/220V(AC), 50/60HZ 30W  |             |              |               |

