



B.N.C.TOOLING Co.,Ltd.

BNC TOOLING.COM
BNC TOOLINGSHOP.COM



HELIOS • PREISSER

1726i / 1734i DIGI-MET® Indicators with integrated wireless



1726 50260



1734 50260

Model

- Aluminium housing
- Outer ring (Bezel) Ø 60 mm
- Replacement probe tip
- M2.5
- Protection class IP42
- Clamping shank Ø 8mm
- Display can be rotated through 280°
- LCD display with 11 mm high numerals
- Factory standard

Functions

- ON / OFF
- Quick-Start
- Quick-Lock (key lock)
- Set to zero at any point
- mm / inch switching
- ABS (display can be set to zero without losing the Preset value)
- TOL (tolerance value input)
- Reversal of counting direction
- Factor input
- Individual key lock
- PRESET-Function (setting a numerical value)
- Variable data output RS
- 232 + Digimatic + USB
- Integrated Wireless

Delivery

- Cardboard box



**integrated
iW wireless**
Wireless Data Transmission



More information on our i-series and Integrated Wireless on page 277

Measuring span mm	Resolution mm inch	Error limit		Repeatability mm	Measuring force N	Order no.
		total span mm	partial span**mm			
12.5	0.0005 .00002	0.004	0.002	0.001	0.65-0.9	1726 50260
25	0.0005 .00002	0.004	0.002	0.001	0.65-1.15	1726 50660

With combined analogue / digital display and MIN / MAX / TIR Function

* Reading switchable: 0.0005 / 0.001 / 0.002 / 0.005 / 0.010 mm

** Partial span= 25 steps by step value 0.0005 mm

1998780

Accessories

Accessories	Order no.
Battery, 3V-Lithium, CR 2450	1998 770
Data cable Data Variable to USB	1998 720
Data cable Data Variable to RS232	1997 501
Data cable Data Variable to digimatic	1998 501
Cable release (12,5 mm)	1739 910
i-Stick USB-receiver for Integrated Wireless	1998 780

Integrated Wireless is intended to be sold in the European Economic Area only

QuickLock QuickStart Waterproof acc. IP Data output DIN

02-918-8020
02-918-8021(Fax.)

089-788-5199
084-8744-883

125

www.bnctooling.com bnctooling@hotmail.com