



MC- 6/7/10 Series

Mini Centrifuge For MC-6/7/10 Low Noise Elaborate



MC-6



MC-7



MC-10

Key Features

1. RCF: 2000xg, 2300xg, 5000xg
2. Max. Rotational Speed: 6,000rpm, 7,000rpm, 10,000rpm

Product Description

Applications:

The MC-6, MC-7, MC-10 is available with some different rotor configurations. The strip tube model holds two 8×0.2ml PCR strip tubes or 16 individual 0.2ml tubes. The standard model accommodates 6×1.5/2.0ml tubes directly and smaller tubes with adapters. Both 0.5ml and 0.2ml adapters are supplied with the standard unit. Operation of the centrifuge begins when the lid is closed. The rotor is quickly accelerated to 6000/7200rpm. Upon opening the lid, the rotor comes to a stop.

Features:

1. Elaborate, colorful outer shell (green, red, blue).
2. Low noise.
3. Carbon fiber rotor.
4. Safe and durable.

Technical Specifications:

Type	MC-6	MC-7	MC-10
Relative Centrifugal force (RCF)	2000xg	2300xg	5000xg
Max. Rotational Speed	6,000rpm	7,000rpm	10,000rpm
Rotors	6×1.5/2.0ml angle rotor 2-8×0.2ml strip rotor Rotor for slide	6×1.5/2.0ml angle rotor 2-8×0.2ml strip rotor	6×1.5/2.0ml angle rotor
Maximum noise	≤50Db		
Power Requirement	30W	30W	40W