



B&N Series AE-C18N2/ C18B2/ C23N2/ C23B2

Autoclave -Class B2/N2 Commonly Used Of Sterilization



Product Description **Class B2 / N2**

AE-C18N2/C18B2/C23N2/C23B2 Series:

Feature:

1. It is fully automatic table top autoclave with pre set programs, with high-precision temperature and pressure controlling;
2. The classB autoclaves complies with European standard En13060;
3. In built independent rapid steam generator ensures quick sterilization cycles;
4. User friendly interface;
5. LCD screen displaying time, temperature and pressure, process alert and instrument conditions;
6. Choice of language settings including: English, Spanish, German, Polish, French, Magyar, Romanian, Dutch, Lithuanian, Latvian, Czech, Italian and Chinese;
7. Easily accessible water tank.;
8. Liquid sterilization program optional;
9. Extra drying program optional.

Technical Specifications:

Model	Type	Power	Chamber Volume	Chamber	Out Size
AE-C18N2	Class N	2100W	18 Liters	Φ247×350	W 480mm/H 455mm/D 600mm
AE-C18B2	Class B	2200W	18 Liters	Φ247×350	W 480mm/H 455mm/D 600mm
AE-C23N2	Class N	2100W	23 Liters	Φ247×450	W 480mm/H 455mm/D 700mm
AE-C23B2	Class B	2200W	23 Liters	Φ247×450	W 480mm/H 455mm/D 700mm

Class N autoclave:

Program	Temp (°C)	Pressure (Mpa)	Sterilization Time (Min)	Total Time (min)
Solid	134	210	4	20-45
	121	110	20	35-60
Liquid	134	210	10	35-60
	121	110	30	35-60
Wrapped	134	210	10	45-65
	121	110	30	50-75
Textile	134	210	10	45-65
	121	110	30	50-75
Prion	134	210	18	45-75
Drying	—	—	—	1-20