NH300 High Quality Colorimeter

- **Humanity Design and Convenient Operation**
- Stable Measurement Performance
- Convenient and Fast Locating
- PC Software -More Function Expansion
- Equipped with High Capacity Li-ion Battery





NH Series High Quality Colorimeter

Color So Rich in Beauty















NH300 High Quality Colorimeter

1. Leading Humanity Design and Convenient Operation

- One-Touch Access to Measurement Interface
- Structure Design in line with Ergonomics
- Easy-to-use Operator Interface

2. Stable Measurement Performance

- The average fluctuation of △E is less than 0.07, actually more in 0.04~0.06.
- Portable structure design is more conductive to keeping the instrument stable when using.

3. Flexible and Accurate Locating

• Ilumination locating is a fast, simple and convenient locating which is created by 3nh.

4. PC Software- Realize More Function Expansion

- 3nh has the intellectual property of PC software. The corresponding software serial number and password protection are configured in 3nh colorimeter.
- Be able to perform color difference analysis, color difference cumulative analysis, chromaticity index, color sample database management, simulating object color, etc.

5. Advanced Power Management Design


- 3nh is the first enterprise using high capacity Li- ion battery in colorimeter.
- 3nh Li-ion battery can be repeatedly charged which will save cost. Meanwhile, it can measure more than 3000 times on one charge to ensure the stability of long time measurement.

E Total Color Aberration

 \triangle L is large stands for the color is partial white. \triangle L is small stands for the color is partial black. \triangle a is large stands for the color is partial red.

△a is large stands for the color is partial red. △a is small stands for the color is partial green

 \triangle b i S large stands for the color is partial yellow. \triangle b is small stands for the color is partial blue.



Applicable Industries



Technical Specifications

lluminatingNiewing Geometry :8/d Measuring Aperture :Ф8mm

Detector: Silicon photoelectric diode

Color Space : CIEL *a*b*C*h* CIEL *a*b* CIEXYZ Color Difference Formula:△E*ab△L*a*b*△E*C*h*

Light Source : D65

Light Source Device: LED blue light excitation Errors Between Each Equipment: ≤0.40△E*ab Storage: 100pcs standards 20000pcs samples

Repeatability : Standard deviation within△E*ab 0.07 Average of 30 measurements of standard white plate

Weight: 500g

Dimension: 205x 70x 100 mm

Power source: Rechargeable lithium-ion battery 3.7V@3200mAh L amp Life: 5 years, more than 1.6 million measurements

