



SJS-5KV

- Dimension:L X W XH (mm)410 X 260 X 1400; Weight:about60kg;Capacity:5000N;Stroke:200mm.
- Testing speed: 1-200mm/min;speed resolution: 1!mm/min.
- Can be configured(purchase additionally):SH/SP(2N-5KN)force gauge, various clamps.

SJS-10KV

- Dimension:L X W XH (mm)480 X 260 X 1400; Weight:about60kg;Capacity: 10000N;Stroke:200mm.
- Testing speed: 1-200mm/min;speed resolution: 1mm/min.
- Can be configured(purchase additionally):SH/SP(2N-10KN)force gauge, various clamps.

SJS-20KV

- Dimension:L X W XH (mm)480 X 300 X 1350; Weight:about75kg;Capacity:2000N;Stroke:200mm.
- Testing speed: 1-100mm/min;speed resolution: 1mm/min.
- Can be configured(purchase additionally):SH/SP(1K-20KN)force gauge, various clamps.

SJS-30KV

- Dimension:L X W X H (mm)480 X 300 X 1350; Weight:about75kg;Capacity:30000N;Stroke:200mm.
- Testing speed: 1-100mm/min;speed resolution: 1mm/min.
- Can be configured(purchase additionally):SH/SP(1K-30KN)force gauge, various clamps.

SJS-50KV

- Dimension:L X W XH (mm)480 X 300 X 1350; Weight:about75kg;Capacity:50000N;Stroke:200mm.
- Testing speed: 1-100mm/min;speed resolution: 1mm/min.
- Can be configured(purchase additionally):SH/SP(1K-50KN)force gauge, various clamps.



SJS-5KV (SP)



SJS-10KV (SP)



SJS-20K~50KV (SP)

SJS-500H

- Dimension: Lx WxH(mm) 590x210x320; Weight: about 29kg.
- Capacity: 500N; Stroke: 210mm.
- Stepless speed adjustment, digit display, vertical test speed: 1-500mm/min;speed resolution: 1mm/min.
- Can be configured (purchase additionally):SH/SP(2N-500N) push pull force gauge, various clamps.



SJS-500H (SH)



SJS-500H (SN)



SJS-500H (SP)

Note : the appearance and color depends on the real product.