



Test Demonstration of Torque Meter



Test Torque Of
Mobile Phone



Test The Dynamic
Frictional Torque
Of Connector



Test Torque Of
Motorized
Screwdriver



Test Torque Of Cap



Test Torque
Of Furniture
Connecting Bolt



Test Torque Of
Volute Spring

	mN.m	(N.cm)	N.m	gf.cm	Kgf.cm	Kgf.m	Ozf.in	lbf.in	lbf.ft
4mN.m	1	0.1	0.001	10.2	0.0102	0.000102	0.142	0.00885	0.000738
1cN.m	10	1	0.01	102	0.102	0.00102	1.42	0.0885	0.00738
4N.m	1000	100	1	10200	10.2	0.102	142	8.85	0.738
1gf.cm	0.0981	0.00981	0.0000981	1	0.001	0.00001	0.0139	0.000868	0.0000723
1kgf.cm	98.1	9.81	0.0981	1000	1	0.01	13.9	0.868	0.0723
1kgf.m	9810	981	9.81	100000	100	4	1390	86.8	7.23
tozf.in	7.06	0.706	0.00706	72	0.072	0.00072	1	0.0625	0.00521
1lbf.in	113	11.3	0.113	1150	1.15	0.0115	16	4	0.0833
1lbf.ft	1360	136	1.36	13800	13.8	0.138	192	12	1

LP-10-C Rubber Long Position Thickness Gauge

LP-10-C Rubber Thickness Gauge is mainly used for measuring the thickness of vulcanized rubber and plastic products. It carry out HG2041-2009 «Technical specifications for rubber thickness gauges) .It has the following characteristics: simple structure, easy usage, reliable quality and removable base.

Characteristics

- Dimension: LX W X H(mm)145 X 195 X 80.
- Test range: 0-10mm, resolution: 0.01mm.
- Diameter of upper probe: 62mm; 65mm; 610mm; 64mm X 1mm.
- Weight quality: 130.0g, 110.0g, 10.0g.
- Weight: about 0.9kg.



LP-10-C

STK Analog Torque Gauge

STK Analog Torque Gauge is an ideal instrument for measuring low torque.

Characteristics

- Contraption, low weight, convenient usage.
- Three-way chuck jaw.
- Double scale indication,reading convenience, two-way scale and two-way test.



STK Analog Torque Gauge

Parameter

Model	STK-0.45	STK-0.9	STK-1.5	STK-3	STK-6	STK-12	STK-24	STK-36	STK-60	STK-90	STK-150
Capacity	0.05~0.45cN.m	0.1~0.9cN.m	0.2~1.5cN.m	0.3~3cN.m	0.6~6cN.m	1~12cN.m	2~24cN.m	4~36cN.m	6~60cN.m	10~90cN.m	20~150cN.m
Resolution	0.01cN.m	0.02cN.m	0.02cN.m	0.05cN.m	0.1cN.m	0.2cN.m	0.5cN.m	0.5cN.m	1cN.m	1cN.m	2cN.m
Accuracy	±5%										
Dimension	φ44×98mm							φ64×130mm			
Weight	About 0.2kg							About 0.5kg			

Note : the appearance and color depends on the real product.