



B.N.C.TOOLING Co.,Ltd.

BNCTOOLING.COM
BNCTOOLINGSHOP.COM



HELIOS • PREISSER

1378 DIGI-MET® Depth gauges for one-handed operation



Model

- Stainless steel
- Inductive measuring system, protection class IP67
- Locking screw
- Factory standard
- Constant measuring force through spring pressure
- Measuring pin with thread M 2.5 for exchangeable measuring inserts for core hole bores, also compatible with dial gauges inserts (see No. 0710) for depth measurement
- Measuring inserts for core hole bores (for additional costs) see table

Functions

- ON / OFF
- Quick - Start
- Quick - Lock (key lock)
- Set to zero at any point
- mm / inch switching
- PRESET - Function (setting a numerical value)
- Variable data output RS 232 + Digimatic + USB

Delivery

- Ball measuring insert for depth measurement

Marked	Measuring range		Reading		Error limit	Order no.
	mm	inch	mm	inch	mm	
	0-60	0-2.4	0.01	.0005	0.02	1378 505
	0-100	0-4	0.01	.0005	0.02	1378 508

Marked = excess length/excess weight


Marked = includes a F.O.C. calibration certificate, traceable to national standards

02-918-8020
02-918-8021(Fax.)

089-788-5199
084-8744-883




1278 Measuring inserts



☒	☒	Thread size mm	Core diameter mm	Diameter mm	Order no.
		M 16 x 1.5	14.38	14.32	1278 923
		M 16 x 1.0	14.92	14.87	1278 924
		M 12 x 1.25	10.65	10.59	1278 936
		M 12 x 1.0	10.92	10.87	1278 938
		M 10 x 1.0	8.92	8.87	1278 940
		M 10 x 0.75	9.19	9.13	1278 942
		M 8 x 1.0	6.92	6.87	1278 944
		M 8 x 0.75	7.19	7.14	1278 946
		M 6 x 0.75	5.19	5.14	1278 948
		M 5 x 0.5	4.46	4.41	1278 950
		M 16	13.84	13.79	1278 952
		M 12	10.11	10.05	1278 954
		M 10	8.38	8.32	1278 956
		M 8	6.65	6.59	1278 958
		M 6	4.92	4.87	1278 960
		M 5	4.13	4.08	1278 962
		16 pcs set			1278 930

1278 Reduction piece



☒	☒	A mm	B mm	Order no.
		6	12.00	1278 912
		9.5	16.00	1278 916
		15	20.00	1278 920