



AE-P Series

Pressure Steam Sterilizer With Portable



AE-PB24
AE-PB30

Key Features

- Intelligent microcomputer control system: Using LED digital control system; After sterilization finished, sterilizer will automatic alarm and shut down.
- Interlock device: The control system can real time supervision the sterilizer chamber's temperature and pressure. Only under the safety temperature and pressure can open the sterilizer's cover. Make sure the operator's safety.
- The structure of cover's opening: Using shift place type of quick-open cover to improve sealing and safety performance.
- Preset program: Can preset fixed program that sterilize the liquid and solid body.
- Memory storage system: Store the last operation program so convenient next operation.
- Digital display screen: Digital display screen and working indicator light display running state.
- Safety devices: Interlock device, overtemperature and over pressure protecting system, burned protection, safety relief valve, current leakage protector and automatic fault detection

Product Description

Product Features of Pressure steam sterilizer:

Intelligent microcomputer control system: Using LED digital control system; After sterilization finished, sterilizer will automatic alarm and shut down.

Interlock device: The control system can real time supervision the sterilizer chamber's temperature and pressure. Only under the safety temperature and pressure can open the sterilizer's cover. Make sure the operator's safety.

The structure of cover's opening: Using shift place type of quick-open cover to improve sealing and safety performance.

Preset program: Can preset fixed program that sterilize the liquid and solid body.

Memory storage system: Store the last operation program so convenient next operation.

Digital display screen: Digital display screen and working indicator light display running state.

Safety devices: Interlock device, overtemperature and over pressure protecting system, burned protection, safety relief valve, current leakage protector and automatic fault detection.

Technical Parameter of Vertical Pressure Steam Sterilizer:

Parameter/Model	AE-PB24	AE-PB30
Configuration	Automatic Control	Automatic Control
Material/Pot wall thickness(mm)	Stainless steel/2.0	Stainless steel/2.0
Volume/GW	24L/25Kg	30L/27.5Kg
Voltage/Power	220V/2Kw	220V/2Kw
Packing size(L x W x H mm)	500 x 500 x 800	500 x 500 x 900
Sterilization chamber volume(D x H mm)	280 x 495	280 x 585
Time setting range	0-999 min	0-999 min
Rated working pressure	0.142MPa	0.142MPa
Sterilization temperature setting range	50~126°C	50~126°C