



SPH Manual Horizontal Test Stand

SPH Test Stand, equipped with push pull force gauge, is with clamp itself and used for compression and tension test/insertion and extraction test/breaking test/level peel-off test. Use on worktable, manual operation,easy and stable.

- Dimension: LX W X H(mm)450 X 185 X 170; Weight: about 9.0kg;Capacity: 500N; Stroke: 60mm.
- Can be configured(purchase additionally): SN, SH/SP (Sensor Inside) push pull force gauge , various clamps.



SPH(SP)



SPH(SN)



SPH(SH)

SLS Peel-off Force Special Test Stand

SLS Test Stand is specially designed for vertical peel-off test. Equipped with force gauge, it is used for testing adhesion for copper foil/tinfoil/aluminum foil and rubberized fabric.

Trapezoidal screw drive, unitary nut design. The moving part is 45 degrees against level, and move with sample together for vertical peel-off test. Manual operation, easy and stable.

- Dimension: LX W X H(mm)420 X215 X 480; Weight: about 22.0kg.
- Capacity: 500N; Stroke: 170mm.
- Can be configured (purchase additionally): SH/SP (Sensor Inside) push pull force gauge, various clamps.



SLS Peel-off Force Special Test Stand

SJS-500S Stepper Motor Peel-off Force Test Stand

SJS-500S is professional vertical peel-off force test stand.Matched to force gauge,especially to test adhesion for copper foil,tinfoil,aluminum foil and rubberized fabric.

Stepper motor inside,accurate test speed,good stability,more effective data.

- Dimension: Lx WxH(mm)510 370X610; Weight: about 59kg.
- Capacity: 500N; Stroke: 200mm.
- Can be configured (purchase additionally): SH/SP (2N-500N) push pull force gauge, various clamps.



SJS Stepper motor Peel-off Test Stand

SPV Manual Hydraulic Test Stand

SPV Test Stand , equipped with push pull force gauge,is specially designed for heavy load test. Manual operation,easy and stable

- Dimension: LX WXH(mm) SPV-50K: 260X450 X 1190
SPV-200K: 260X470 X 1320
SPV-500K: 338X490 X 1460.
- Capacity: 50~500KN.
- Stroke: SPV-50K: 120mm;SPV-200K: 140mm; SPV-500K: 180mm
- Weight: SPV-50K: 103.0kg;SPV-200K: 200kg;SPV-500K:376kg.
- Can be configured(purchase additionally): SP/SH(10kN-500kN) push pull force gauge, various clamps.



SPV-50K



SPV-200K

Note : the appearance and color depends on the real product.